## X-BOLT 120 30




\* Non-binding image

## **DESCRIPTION / GEOMETRY**

Reliability, autonomy and an enviable aesthetic to enjoy your weekend adventures. If you think about technology and performance, if you think about expanding your horizons without complexes... this is, without a doubt, your best option.

An advanced **G2** carbon frame with intermediate module and internal battery, an efficient 120 mm suspension design and the potential of the fourth generation Bosch drive system make this bike a benchmark in the ebike segment. The 29" wheels together with the agility and lightness provided by its innovative chassis will allow you to devour kilometers and kilometers without any worries.

If you think of a balanced geometry, if you think of a fast, fun and stable bike... you are thinking of **X-BOLT 120**.



	120mm S	M	L
L ejes(A)	1183	1214	1245
L tubo superior(B)	584	603	626
L tubo virtual(C)	-	-	-
L tubodirección(D)	110	125	140
L centro/centro(E)	-	-	-
L centro/tope(F)	406	457	508
L vainas(G)	457	457	457
L avance(H)	51	51	51
H pedalier(I)	37	37	37
ß dirección(J)	67°	67°	67°
ß tubo vertical(K)	76°	76°	76°
Reach(L)	435	459	484
Stack(M)	609	622	636
Trail(N)	99	99	99

## **SPECIFICATIONS**

Frame	X-Bolt - G2 Carbon Concept Frame. Intermediate modulus carbon fiber. Several molds. TA 12mm. Internal Cable Routing. Boost. Post Mount. Full Integrated Battery. Head tube 1.5 Tapered.
Fork	Rock Shox 35 Silver Air Crown 15 Boost. E-bike. Travel 120mm. Tapered.
Shock	Rock Shox Deluxe Select R 120 E-bike
Headset	Ritchey Pro Integrada Tapered 1.5
Shifter	Sram SX Eagle 12v
Shifters	Sram SX Eagle 12v
Brakes	Shimano MT-400 180/180
Crankset	Fsa Forged E-bike 34
Cassette	Sram SX PG-1210 Eagle 12v 11-50
Chain	Sram SX Eagle 12v
Wheels	Mavic E-DEEMAX 29 30 CL
Tires	Hutchinson Griffus TLR Sideskin 29x2.50
Stem	Race Face Ride 35
Handlebar	Race Face Ride 35 760mm 10mm Rise
Seat post	Race Face Aeffect R Dropper 125mm 30.9
Saddle	San Marco GND Dynamic
Motor	Bosch Performance Line CX
Display	Bosch Purion / Bosch Power Tube 625

<sup>\*</sup> The specifications are subject to change without prior notice and are not binding

## **OPTIONS COLORS**



